



- After a maximum tree has been created, it is pruned back using biasvariance trade off. What does pruning offer us? It offers
  - a. adding more features to balance the bias-variance trade off.
  - b. increasing the depth of the tree to capture more detailed patterns in the data.
  - c. reducing the tree's size to avoid overfitting and enhance generalization.
  - d. Increase the trees complexity by adding more branches and nodes.





- In DTs, we need to clearly define the rule for determining if a node is a terminal one. The rule can be \_\_\_\_\_
  - a. A random node can be determined to be a terminal node.
  - b. The node that is pure and cannot be further split.
  - c. The node that has the highest number of instances within the dataset.
  - d. The node that has the lowest purity measure among all nodes.





- In Random Forest, each tree is the result of applying the CART method to a selection of attributes/features at each node. The selection is
  - a. Based on their order in the dataset.
  - b. Based on their importance.
  - c. Randomly from the entire dataset.
  - d. Randomly from the training dataset.





- Random Forest cannot predict (regression) beyond range of input parameters because
  - a. RF is trained to capture relations and patterns within the observed range only.
  - b. The ensemble nature cannot reduce overfitting and provide robustness.
  - c. RF lacks the ability define significant parameters.
  - d. RF requires additional training to predict beyond the range of input parameters.

    The parameters additional training to predict beyond the range of input parameters.

    The parameters additional training to predict beyond the range of input parameters.

